HAHN Lamellen		Louvre window S9-iV				
status:		enquiry	order			
project number:			purchase order:			
project manager:			phone number:			
desired delivery date:			date:			
project:					de	9 9
delivery address:					outside	inside
contact person on site:					0	
Pos.:		01	02	03		
	no.:					
frame dimensions	width: (mm)					
	height:					
	type of frame:	type 1	type 1	type 1		
		type 2 type 3	☐ type 2 ☐ type 3	 type 2 type 3		
fra		thickness:mm (see detail glazingprofile)	thickness:mm (see detail glazingprofile)	thickness:mm (see detail glazingprofile)		
	no. of blades:					
	thickness:	24mm	24mm	24mm		frame dimensions height
Φ	type of filling:		double glazed	double glazed		
l typ	glass design:	insulated blades	insulated blades	insulated blades		me dii
blade panel type	standard:	outer side: mm		outer side: mm		
	air space: 16mm	air space: mm inner side: mm	air space: mm inner side: mm	air space: mm inner side: mm		
٥	inner side: 4mm type of glass:					
	finish:	powder coated	powder coated	powder coated		
finish	colour supplier	natural anodised	natural anodised	natural anodised		
=	& colourcode:					
	type of control:	manual electric V	manual electricV	manual electric V		
		pneumatic	pneumatic	pneumatic		
v	description: cable length:					
controls	(standard = 2,5m)	m	m	m		
	cable exit: (LAH 65 only)	top bottom	top bottom	☐ top ☐ bottom	Гионо	
	control	side through frame position A (right side)	side through frame position A (right side)	side through frame position A (right side)	Frame type 1	
	position:	position B (left side)	position B (left side)	position B (left side)	<u>., </u>	46.8
	fixing brackets /	height mm	height mm	height mm		
special adaptor: smoke vents		yes	yes	yes		
CE- certified:		no	no no	no	Frame	TIME
					type 2	
1	ame (A)	inside	B			
typ	<u>be 1</u>					4 8
				46.		
	51.	5		_ 		20 21 - 10 - 10
	- 01.	frame dimensions width				
Fra	ame """	Frame type 3			Frame	
	<u>pe 2</u>				type 3	
	0		.0.25			
	18	51.5	51.5			
Sonta	mhar 2027, / Subject	to change without notice	- 01.0	4		